

Revision Date: 04/20/15 MSDS Number: 19023 Wilsonart® PVA Wood Glue Series Page 1 of 4 Revision No: 6

PRODUCT AND COMPANY IDENTIFICATION

Common Name: Wilsonart® PVA Wood Glue Series

Includes: Wilsonart® 10 Adhesive
Wilsonart® 20 Adhesive
Wilsonart® Type II Adhesive Lokweld[®] White Glue (10) Lokweld® Type II Glue

Manufacturer: WILSONART LLC

P. O. BOX 6110 - 2400 WILSON PLACE

TEMPLE, TX 76503

INFORMATION PHONE: 800-433-3222 (USA)

Trade Name: WA PVA Wood Glue

Material Uses: Adhesive for laminate

In Case of Emergency Contact CHEMTREC: 800-424-9300 (USA)

703-527-3887 (INTERNATIONAL)

2 **HAZARDS IDENTIFICATION**

Route of Entry: Skin, eyes, inhalation, ingestion.

Target Organs: None.

Skin Contact: May cause skin irritation. Preexisting skin conditions may be aggravated by exposure to this

material

3

1


Eye Contact: May cause eye irritation.

Inhalation: Breathing vapors may cause irritation to the respiratory tract. Preexisting respiratory conditions

may be aggravated by exposure to this material.

Ingestion: Not an expected route of entry. If ingested it may cause irritation to the gastro-intestinal tract.

HMIS (United States):		
HEALTH	1	
FLAMMABILITY	1	
REACTIVITY	0	
PPE	В	



WHMIS (Canada): Not Classified as Hazardous

COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS#	% by Weight
Vinyl Acetate Polymers (Type II)	Not Applicable	40 - 70
Vinyl Acetate Polymers (10, 20)	9003-20-7	40 – 70
Water (10, 20, Type II)	7732-18-5	30 - 60
Polyvinyl Alcohol (10, 20)	25213-24-5	3 – 7
Aromatic Diester (10, 20)	NJTSRN 990011	1 – 5
Aluminum Chloride (Type II)	7446-70-0	0.5 - 1.5

MSDS Number: 19023 Revision No: 6 Revision Date: 04/20/15 Page 2 of 4

4 FIRST AID MEASURES

Skin Contact: Remove contaminated clothing and wash affected areas with soap and water. If irritation develops, seek medical attention.

Eye Contact: Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush. Seek medical attention.

Inhalation: Remove patient to fresh air. If patient is having difficulty breathing, seek immediate medical attention. If not breathing, clear airway and start mouth-to-mouth artificial respiration (or use bag-mask respirator). Seek immediate medical attention.

Ingestion: DO NOT induce vomiting. Seek immediate medical attention. DO NOT give anything by mouth to an unconscious person.

5 FIRE FIGHTING MEASURES

Flash Point: Not Applicable.

Flash Point Method: Not Applicable.

Autoignition Temp.: Not Applicable.

Burning Rate: Material is not flammable.

Flammability Classification: Combustible Liquid Class IIIB. Dry adhesive will burn.

Firefighting Equipment: Use self-contained breathing apparatus (SCBA) with a full-face piece and pressure demand or other positive-pressure mode and protective gear appropriate for surrounding materials. In case of fire, use water, dry chemical, CO₂, or alcohol foam extinguishing media.

Hazardous Products of Combustion: Carbon Oxides (CO and CO₂), Aldehydes, Acetic Acid, Sulfur Oxides, Chlorine, Hydrogen Chloride, and various Hydrocarbons.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate PPE. Make sure area is well ventilated. Spilled adhesive may be slippery.

Environmental Precautions: Keep out of sewers and drains.

Clean-Up Methods: Dike and contain spill. Absorb spilled product with vermiculite, dry sand, or earth. Place in a suitable non-leaking container and tightly seal for disposal.

7 HANDLING AND STORAGE

Handling Precautions: Wear appropriate PPE. If used indoors, make sure to provide adequate ventilation to prevent vapor build-up. Avoid breathing of vapors.

Storage Requirements: Store in a cool, dry, well-ventilated area. Avoid freezing temperatures. Minimize contact with atmospheric air to prevent inoculation with microorganisms.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use in a well ventilated area. Ensure that a working eyewash and safety shower are in the work area.

Protective Equipment: Wear safety glasses with side shields, and neoprene or rubber gloves.

Exposure Guidelines / Other:

Product Name Exposure Limits

Aluminum Chloride (CAS 7446-70-0) ACGIH TLV: TWA 2 mg/m³ (as soluble salt)

Consult local authorities and local regulations for exposure limits.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid – color varies by adhesive grade.

Physical State: Liquid Odor: Mild sweet

Autoignition Temp.: Not Applicable **Boiling Point:** Similar to water

Composite Partial Pressure: Not Applicable

MSDS Number: 19023 Revision No: 6 Revision Date: 04/20/15 Page 3 of 4

Flash Point: Not Applicable

Freezing / Melting Point: Similar to water

Molecular Weight: Not Applicable **Percent Volatile:** Not Available **pH:** 4 – 5 (10 & 20); 2.9 – 3.1 (Type II)

Solubility: Soluble in Water

Specific Gravity / Density: 1.07 – 1.10 (10, 20); 1.07 – 1.09 (Type II)

Vapor Density: Equivalent to water Vapor Pressure: Equivalent to water

VHAP: Not Applicable

VOC: < 20 g/L

Viscosity: ~ 5600 cP (10); ~ 4750 cP (20); ~ 4900 cP (Type II)

10 STABILITY AND REACTIVITY

Stability: Product is stable as supplied.

Conditions to Avoid: Freezing and boiling temperatures.

Materials to Avoid (Incompatibility): Strong acids, strong bases, oxidizers, reducing agents, copper and

copper alloys.

11

Hazardous Decomposition Products: Carbon Oxides (CO and CO₂), Aldehydes, Acetic Acid, Sulfur Oxides,

Chlorine, Hydrogen Chloride, and various Hydrocarbons.

Hazardous Polymerization: Will not polymerize.

TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals:

Aluminum Chloride (CAS 7446-70-0): Oral LD50 = 370 mg/kg (rat).

Dermal LD50 > 2000 mg/kg (rabbit).

Polyvinyl Alcohol (CAS 25213-24-5): Inhalation 1 hour LC50 > 20 mg/m³ (rat).

Oral LD50 > 5000 mg/kg (rat).

Chronic Toxicity to Animals: No additional information.

Acute Toxicity to Humans: No additional information.

Chronic Toxicity on Humans: No additional information.

Carcinogenic Effects: No additional information.

Mutagenic Effects: No additional information.

Teratogenic Effects: No additional information.

Developmental Toxicity: No additional information.

12 ECOLOGICAL INFORMATION

Ecotoxicity: Not Available. Not expected to be ecotoxic.

BOD5 and COD: Not Available. **Biodegradable / OECD:** Not Available.

Mobility: Not Available.

Toxicity of the Products of Biodegradation: Not Available.

Special Remarks on the Products of Biodegradation: Not Available.

13 DISPOSAL CONSIDERATIONS

Absorb spilled product with vermiculite, dry sand, or earth and allow to solidify. Dispose of solid material in a suitable container.

Dispose of in accordance with Federal, State, and local regulations.

14 TRANSPORT INFORMATION

Restrictions: None known.

DOT Requirements: Not a DOT controlled material (United States).

MSDS Number: 19023 Revision No: 6 Revision Date: 04/20/15 Page 4 of 4

DOT Classification: Adhesive Resin Compound.

Markings: None.

Packaging Requirements: Keep from freezing.

ADR Requirements: Not an ADR controlled material (Europe).

IMDG Requirements: Not an IMDG controlled material.IATA Requirements: Not an IATA controlled material.Marine Pollutant: Not expected to be a marine pollutant.

15 REGULATORY INFORMATION

U.S. Federal Regulations

Chemical (& CAS Number)	SARA 302	SARA 304	SARA 313	CERCLA	CAA 112(r)	RCRA
	(EHS)TPQ	(EHS)Rq	De minimis	Rq	TQ	Code
None						

All quantities in pounds

State Regulations

Chemical (& CAS Number)	CA	MA	MN	NJ	PA	RI
	Prop 65	RTK	RTK	RTK	RTK	RTK
Aluminum Chloride (CAS 7446-70-0)		Х		Х	Х	X

International Regulations

DSL (Canada): The chemicals in this product are listed. **EINECS:** The chemicals in this product are listed.

WHMIS: Not classified as hazardous.

16 OTHER INFORMATION

Changes to this Revision: Section 3-Composition and Section 15 Regulatory. **Prepared by:** Environmental, Health, and Safety Department, Wilsonart LLC.

Telephone: 254-207-7000 Internet: www.wilsonart.com

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF MSDS DOCUMENT